ROYAL 15 M 38 BC Lithium

COMPACT WALK BEHIND SCRUBBER DRYERS ROYAL 15 SERIES

Royal 15 is the compact walk-behind scrubber-dryer ideal for cleaning small and medium-sized surfaces such as stores, laboratories, offices and restaurants. With its 15-liter capacity and 385 mm cleaning width, it provides a productivity of up to 1,540 m²/h. The sturdy and practical aluminum tiltable handle allows maximum manoeuvrability in tight spaces. The design is also carefully studied in every detail to ensure maximum comfort for the operator: the clean lines defining a compact structure and the use of practical compartments in which to store all protruding parts of the machine (such as hoses and cables) help improve the machine manoeuvrability. The use of the machine is simple and facilitated by the practical and intuitive control panel that allows control of its main functions. The ECO SYSTEM program reduces consumption and eliminates waste while maintaining the best cleaning performance with the utmost respect for the environment. The low noise level, guaranteed by the silent mode function, makes Royal to be perfect for day cleaning in "sensitive" environments (hospitals, nursing homes, schools). The lithium-lon batteries in standard equipment have a longer service life and lower maintenance than conventional batteries. They can be recharged at any time, even only partially during short breaks in use, without being damaged. The on-board charger also helps increase productivity because it makes it possible to recharge the machine wherever a power outlet is available, avoiding unnecessary waste of time. Available in two full package versions (BC Lithium and BC Lithium Plus), Royal is capable of up to 2 hours of running time in the BC Lithium Plus version.

Eco System

385

477

1540 - 924

Battery 24V













1





Adjustable and tiltable handle

Control panel with

Removable lid + floater + motor protection filter

Compact squeegee: Large diameter nonmarking wheels

Lithium batteries

Fasy access to main components

TYPE

FEATURES

PRODUCT IDENTIFICATION

display

perfect drying performance even in curve

REF. NO. 13.4050.00 15.4050.00

| TANK | | | | |
|-------------------------------|----|---------------------------------------|--|--|
| Туре | | Double tank | | |
| Cleaning solution tank | 1 | 15 | | |
| Recovery tank | | 17 | | |
| Weight (empty/with batteries) | Kg | 45 - 47,15 (*) / 45,4 - 48,55 (**) | | |
| Dimensions | mm | 772x477x731 | | |

PIECES/PALLET

STANDARD ACCESSORIES

| TYPE | REF. NO. |
|--------------------------------------|------------|
| Filling hose | 30.0369.00 |
| 15" Polypropylene brush ø 0.7 | 40.0008.00 |
| Set front/rear para squeegee blades | 96.0218.00 |
| On board battery charger 24V 5A (*) | 18.0104.01 |
| Lithium battery 24V 312Wh (*) | 18.0107.00 |
| On board battery charger 24V 9A (**) | 18.0103.01 |
| Lithium battery 24V 547Wh (**) | 18.0108.00 |
| 2 | |

OPTIONAL ACCESSORIES

| ТҮРЕ | REF. NO. |
|---|------------|
| 15" Polypropylene brush ø 0,5 | 40.0408.00 |
| 15" Polypropylene brush ø 0,9 | 40.0108.00 |
| 15" Tynex brush grit 240 - ø 0,9 | 40.0208.00 |
| Pad holder 355 mm (for 15" pad) | 40.1008.00 |
| Set front/rear polyurethane squeegee blades | 96.0218.01 |
| Splashguard with bristles | 96.0211.00 |

(*) For Lithium version (**) For Lithium PLUS version

I

*) Silent mode function

qhibli & wirbel 135



| i onoi ouppiy | | Dattory EIV |
|-------------------------------------|---------------------------|-----------------------------------|
| Installed power | W | 470 |
| Advancement | | Manual |
| IP code | | IPX3 |
| BATTERIES | | |
| Туре | | 24V 312Wh (*) - 24V 547Wh (**) |
| Running time | h - min | 1h (*) - 2h (**) |
| Battery compartment dimensions x No | mm x No | 154x233x134 X 1 |
| BRUSHES | | |
| Pad diameter x No | mm - inch x No | 385 - 15"x1 |
| Motor rating x No | W x No | 280 x 1 |
| Motor speed | rpm | 130 |
| Down pressure - Contact pressure | Kg - g/cm ² | 39 - 52 |
| TRACTION | | |
| Motor rating | W | |
| Driving speed | Km/h | |
| Hill climbing ability (full load) | % | 2 |
| VACUUM | | |
| Motor rating | W | 150 |
| Vacuum | mbar - mmH ₂ 0 | 140 - 1427 |
| Airflow rating | l/s | 21 |
| Noise level | dB(A) | 64 / 61 (***) |